

# Installation Guidelines

**PRODUCT NUMBER**  
**CONTAINER SIZE**  
23200 Qt./23100 Gal

**COVERAGE:** 350-500 square feet per gallon depending on surface porosity.

## USE ON:

Use on porous contaminated surfaces. Do not apply to mirrors, windows, plastic, and leather.

## LIMITATIONS:

Use ONLY for removing odors caused by: fire, cigarette/cannabis smoke, pet urine, sweat, decaying food waste, mold, mildew, and body odor.

**This will NOT eliminate odors such as formaldehyde, most VOCs, essential oils, air fresheners, or perfumes.** Safechoice products are made without formaldehyde preservatives. Do not contaminate. Store in airtight containers. Do not freeze.

## SURFACE PREPARATION:

Prior to treatment, ensure the area is thoroughly clean and the source of the odor is removed.

## APPLICATION:

First, ensure the area is as clean and dry and the source of the odor is removed to the best of your ability. Use a safe cleaner like Safechoice All Purpose Cleaner and Degreaser. OdorOut is not a substitute for a cleaner. Next, spray directly on the offensive odor with fogger or spray bottle. For porous surfaces, insure liquid is absorbed into the surface and let dry. For hard surfaces, always wipe off excess immediately after treatment to avoid a liquid build up. OdorOut will continue to work on hard surfaces even after it is wiped off because it will leave a microscopic layer of modified silica on the surface. This layer will continue to contribute to neutralizing odor molecules on the surface. Odor out will continue to absorb and break down odor molecules over time, even after it is wiped off on hard surfaces.

How long will it last? Generally, the effectiveness of OdorOut will last for days or sometimes weeks but cannot be guaranteed. It depends on the severity of the smell, the cleanliness and porosity of the surface, and the amount of ventilation. If the source of the smell can't be eliminated, then a second application may be necessary. If the surface is dirty and porous and the source of the odor cannot be removed, additional cleaning will be required. OdorOut outlasts most products on the

market which means fewer applications and better air quality for you and your family. OdorOut contains 5% amorphous silica which may leave a small residue on any hard surface, e.g. tile, toilets, countertops, glass, mirror etc. This may be noticeable and therefore OdorOut must be wiped off hard surfaces. It will not harm the surface, but may require additional work to remove if left to dry. This is different for porous surfaces because it will not be noticeable. However, should excess liquid be sprayed on fabric multiple times, for example, it could stiffen the fabric slightly.

OdorOut should be stored in plastic containers and not anything made with aluminum, copper or untreated steel. Shelf life is about two years. Depending upon the porosity of the surface, one quart will cover apx. 87 - 125 square feet, one gallon will cover 350-500 SF. Application of OdorOut should be done at temperatures above 41 degrees F.

## CLEAN-UP:

Clean tools and equipment while they are still wet with a warm soapy water solution.

## DRYING/CURING TIME:

30-60 minutes in normal conditions. Normal conditions include a dry surface, access to fresh air flow, moderate humidity, and temperatures above 41 degrees F.

## HEALTH PRECAUTIONS:

As with all coatings and sealers, keep container tightly closed and out of the reach of children. Do not take internally. Keep from freezing. Always use adequate ventilation.

## PHYSICAL DATA

VOC Material: 0 g/l

HAP's (Hazardous Air Pollutants) zero



**LIMITED LIABILITY:** Liability, whether express or implied, is limited solely to replacement of product shown to be defective when applied in accordance with instructions and shall under no circumstances include liability for labor costs or consequential damages. It is the user's responsibility to determine the suitability and safety of the product for its intended use. This limited warranty may not be modified or extended by manufacturer's representatives, distributors, or dealers of AFM products. We particularly recommend that users always test in small inconspicuous areas before application to the entire surface. **American Formulating and Manufacturing** 3251 Third Ave., San Diego, CA 92103 [www.afmsafecoat.com](http://www.afmsafecoat.com).